Structural Performance of the Hotel Grand Chancellor

Peer Review for the Commission

William T. Holmes

Structural Engineer, San Francisco

 General agreement on failure caused by a heavily loaded and lightly reinforced wall.

- General agreement on failure caused by a heavily loaded and lightly reinforced wall.
- The content of the investigative report results in questions with answers not available or not on the record

- General agreement on failure caused by a heavily loaded and lightly reinforced wall.
- The content of the investigative report results in questions with answers not available or not on the record
 - The report relied on simplified analysis techniques apparently due to complexity of building—particularly very strong vertical discontinuity (walls to frame)
 - The derivation of drifts estimated from displacement spectra not clear—certainly not the vertical distribution of drifts (Section .5.2)

- General agreement on failure caused by a heavily loaded and lightly reinforced wall.
- The content of the investigative report results in questions with answers not available or not on the record
 - The report relied on simplified analysis techniques apparently due to complexity of building—particularly very strong vertical discontinuity (walls to frame)
 - The derivation of drifts estimated from displacement spectra not clear—certainly not the vertical distribution of drifts (Section .5.2)
 - The derivation of loading on the failed wall D 5-6 is not clear (Section F.1).
 - Very high vertical accelerations are noted in the February event, but their relative contribution to the failure is not estimated. In fact, it is stated that the wall probably would have failed anyway.

 Although the shaking intensity in the period range of the structure was more intense in September 2010, than in Jan 2011, the explanation of the lack of damage in Sept is not satisfying.

- Although the shaking intensity in the period range of the structure was more intense in September 2010, than in Jan 2011, the explanation of the lack of damage in Sept is not satisfying.
- "Maximum possible displacements" are estimated at 700 mm in Sept and 1050 mm in Feb using average of four elastic spectra from recordings. Two of the four recordings in Sept would have also yielded 1000 or more mm and one of the records from Feb only yielded a maximum of 850 mm.

- Although the shaking intensity in the period range of the structure was more intense in September 2010, than in Jan 2011, the explanation of the lack of damage in Sept is not satisfying.
- "Maximum possible displacements" are estimated at 700 mm in Sept and 1050 mm in Feb using average of four elastic spectra from recordings. Two of the four recordings in Sept would have also yielded 1000 or more mm and one of the records from Feb only yielded a maximum of 850 mm.
- Reference to paper by Pampanin and others as explanation is unclear.

- Although the shaking intensity in the period range of the structure was more intense in September 2010, than in Jan 2011, the explanation of the lack of damage in Sept is not satisfying.
- "Maximum possible displacements" are estimated at 700 mm in Sept and 1050 mm in Feb using average of four elastic spectra from recordings. Two of the four recordings in Sept would have also yielded 1000 or more mm and one of the records from Feb only yielded a maximum of 850 mm.
- Reference to paper by Pampanin and others as explanation is unclear.
- Comparison of inelastic displacement spectra with estimated displacement is Sept do not agree.




Figure 12. Displacement Response Spectra
Christchurch Hospital, 4 September 2010- North 01° West Component




Figure 13. Displacement Response Spectra Christchurch Botanic Gardens. 4 September 2010- South 01° West Component






Figure 14. Displacement Response Spectra
Christchurch Cathedral College. 4 September 2010- North 26° West Component




Figure 15. Displacement Response Spectra Resthaven. 4 September 2010- North 02° East Component

Possible Explanations

- Direction of strongest motion in Sept was NS which minimizes interaction with global moment from cantilevers on east face (potential ratcheting). In Feb, strongest was EW.
- Damage in September in frame superstructure was greater than reported.
- Inelastic spectra at base of upper moment frame was filtered by walled base structure in some way that response was miminized. Brittle Wall D5-6 did not go past its failure point (but did in February)

 Irregular structures, if allowed, must be carefully designed (peer review?)

- Irregular structures, if allowed, must be carefully designed (peer review?)
- "Late" changes in design must be carefully considered (another bad example of bad things happening is the Kansas City walkway that collapsed)

- Irregular structures, if allowed, must be carefully designed (peer review?)
- "Late" changes in design must be carefully considered (another bad example of bad things happening is the Kansas City walkway that collapsed)
- Structures that incorporate major elements affected by shaking in two directions must be carefully considered (most structures designed one direction at a time).

- Irregular structures, if allowed, must be carefully designed (peer review?)
- "Late" changes in design must be carefully considered (another bad example of bad things happening is the Kansas City walkway that collapsed)
- Structures that incorporate major elements affected by shaking in two directions must be carefully considered (most structures designed one direction at a time).
- Interaction of gravity framing with lateral load system must be carefully considered (leaning columns, massive amounts of cantilevers, etc) including the potential for ratcheting.