
Canterbury Earthquake Royal Commission Hearings - 12-15 March 2012 Damage-Resistant Technologies for Improved Seismic Performance of Buildings: an Overview








Stefano Pampanin

Department of Civil and Natural Resources Engineering University of Canterbury











Izmit-Kocaeli, 1999
(photo courtesy: Berkeley Library)

L'Aquila, 2009 (photo courtesy: Anna Brignola)

Christchurch, 2011 (photo courtesy: Kam Weng)











Extensive (beyond reparability?) damage to modern Buildings

Typical plastic hinges in beams (intended to act as sacrificial fuses)
















arch Platform: Resilient Buildings and Infrastructure



Shear walls













National Hazard Research Platform: Resilient Buildings and Infrastructure





prepared for:

Civil Defence Building Safety Evaluation Project


The Past and Present: a Factual Damage Report






<u>Edited by:</u> Assoc Prof Stefano Pampanin Wong Yuan Kam

Contributing Authors: Umut Akguzel Weng Yuen Kam Sahin Tasligedik


















Damaged buildings (22 Feb 2011)
















Number of Buildings in Demolition List: 1300-1400



As per 12 June 2011 Source: CCC Data (Kam, Pampanin, Elwood, 2012)















Bigger than "code-design" level....





Higher than expected displacement demand...















Fallacy n.2:

"The earthquake does not read the seismic codes."

- late Prof Tom Paulay













Fallacy n.3:

"How many unknown faults are still there?" -(Almost everyone)













Facts: The Higher Expectations from the Society

- No victims nor collapse (Deaths)
- Minimum level of damage or direct costs (<u>Damage</u> = <u>Dollars</u>)
- Minimum business interruption and recovering (indirect) costs (<u>Downtime</u>)














Current Performance-Based Design Philosohy





Earthquake Design Level











Fallacy

The Code-Standard is **NOT** meant to be used as a Target or Ultimate Goal but as a minimum by law

Corollary:

An Earthquake-Proof Building (following minimum standards and traditional technology) is likely **NOT** to be as "earthquake proof" as people think/wish














Let us Raise the Bar















Some Good News

Significant Progress in Building Technology for Damage-Resistant Solutions has occurred in the recent past, as per other fields (albeit a bit slower)














The Opportunity for the Future: the best know-how for the rebuild

Base Isolation

(Christchurch Women Hospital)

PRESSS-Technology (Southern Cross Hospital Endoscopy Building)

















C.A.S.E Project (L' Aquila Italy – 2009)



Base Isolation combined with Basement for Car-parking

*To house 18000 people semipermanently. *3 months to completion of 1st blocks.











Associate Professor Stefano Pampanin

National Hazard Research Platform: Resilient Buildings and Infrastructure





Base Isolation for residential

Sliders



Why not using Kiwi
(shall we say kiwItalian?)
Technology and
Manufacturing for the
Christchurch rebuild?














New Generation of Damage-Resisting systems



- **Jointed Ductile** DRY connections assembled by post-tensioning techniques
- inelastic demand accommodated within the connection
- <u>Hybrid systems</u>: combination of unbonded post-tensioning AND dissipaters
- "Controlled Rocking":
 - Reduced level of damage
 - Negligible residual (permanent) deformations (recentering)




PRESSS-Technology (PREcast Seismic Structural System)




Five-Storey Test-Building (UC San Diego, Aug 1999, coordinator Prof. M.J.N. Priestley)









Extensive Laboratory Testing: Frames




University of California at San Diego PRESSS Program



University of Canterbury Amaris et al., (2004-2008)




Extensive Laboratory Testing: Walls



UC San Diego (Priestley et al., 1999)


University of Canterbury (Marriott et al., 2005-2009)

U-shape Flexural Plates






Traditional (monolithic)



New generation

(rocking temples)













Slide 26


A2 Author, 16/10/2008

Conventional VS.


Rocking-Dissipative

Seismic action Coupled Walls





(a) Relative vertical displacement in adjacent walls




Seismic action

(d) Coupled hybrid walls

Historical Developments in Seismic Design

PAST (pre-1970s codes)

PRESENT (post-1970s codes) CHRISTORIUS CODES COD



After Capacity Design

SE I SMS I C

NZ S 3101

17 AUG 2004

4 % DR I FT.

UNIVERSITY OF

CANTERBURY

OF TO SE I SMS I C

OF TO SE I SMS I C

NZ S 3101

17 AUG 2004

FUTURE (Next Generation of codes: NZ 3101:2006 (Appendix B)





National Hazard Research Platform: Resilient Buildings and Infrastructure



Learning From our Ancestors













Destruction of Sparta in 464 B.C. (frame by Egisto)













Vulnerability of towers





Napoli, 1806

Tuscany, **1896**
















Medieval Tower transformed into a private apartment (Pavia, Italy)





Use of post-tensioning for retrofit/repairing
(Shape-Momory-Alloys)





Use of post-tensioning for retrofit













National Hazard Research Platform: Resilient Buildings and Infrastructure



Very effective Earthquake-resistant systems CANTERBURY THE WINDER STATE OF THE PROPERTY OF THE

in the past...(rocking marbles blocks) **Rocking Section**

Multi-block Rocking: Ancient Greek Columns (Athens, Acropolis)







One Further Step Ahead


REPAIRABILITY


OF THE

WEAKEST LINK OF THE CHAIN

Repleacable Dissipaters ("Plug & Play")










Amaris et al. 2006





Instructions post-aftershock?

(simply check and, if required, replace your Plug&Play dissipater as you would do for a light bulb)





Ordinary steel



Viscous damper

National Hazard Research Platform: Resilient Buildings and Infrastructure



From theory... to Practice













Codes and Design guidelines are available
















On-site Applications (1)





Paramount Tower, San Francisco (Englekirk, 2002)













Brooklyn System – Italy (Pampanin, Pagani, Zambelli, 2004)



On-site Applications (3)





Mendoza, Argentina

On-site Applications (4)








Costarica, Holcim Producto de Concreto








On-site Applications (5)



MacDiarmid Building

Victoria University, Wellington





Associate Professor Stefano Pampanin

National Hazard Research Platform: Resilient Buildings and Infrastructure



NZ Concrete Industry Rotorua, 2-4 October 2008

PRESSS Ltd.




21st Century Precast: the Detailing of NZ's First Multi-storey PRESSS Building

Alistair Cattanach

Dunning Thornton Consultants Ltd.

Stefano Pampanin

PRESSS Ltd./University of Canterbury

















PRESSS Ltd.

The Building:

6000m2 Teaching and Research Laboratories

+ Basement Carparking and Storage

Architect: Jasmax + Labworks

Building Services/Fire: Beca

Contractor: Mainzeal (Staged Procurement)

Precast Sub: Concrete Structures Ltd.

Project Budget: \$40M (Large Lab Component)











National Hazard Research Pl Associate Professor Stefano Pampanin





earch Pla

concrete award

Dunning Thornton Consultants

Alan MacDiarmid Building, Victoria University of Wellington

The Allan MacDiannid Building is the first multi-storey PRecast Sesmic Souctural Systems (PRESSS) building in New Zestand

The result of positive collaboration between engineers, academia and contractors, it implements a new technology in seismic and component-based concrete construction.

PRecept Seamic Sourceural Systems use un-bonded, post-tensioning and rocking joints within the structure to enume the building returns to upright without significant structural damage, even after a major seamic event.

For Victoria University as a long-term building owner, this system provides

- a significantly reduced cost, aggregated over the bille of the building, to repair potential seamic clamage. This comes from reducing displacements under small earthquakes with the high pre-rocking soffness of the pre-seried system, and from concernating the seamic damage in replaceable energy dissipates of when that throughout the structure for larger events.
- leakaged in-building accelerations once too lang occurs, the to the feelbling in the superstructure, to almost those of a base inclued building at a faction of the cost in a science research building where the fit-out and services can be of higher value than the building disett, this is a huge advantage.

The fully precast system more than equals its steel alternatives in speed, ecousing, self-in, quiet execution and sesurity performance. The capped rocking walls and the semonotifie-replacible disaptems are world from. Entrent: Dunning Thornton Consultants Owner: Victoria University of Wellington Architect: Assmar

Consulting Engineer: Dunning Thornton Consultants Contractor: Alainseal



What the judges said

If it artifieds fitting that the Victoria University of Workington Alon MacDomnid building trained offer the extenses Nobel Price extenses artified by should incorporate cutting edge to brinking and the brinking.

This is the Arst time in New Zeeland that anistic distinguished distinguished with the News of set banded just for anisting and reaching just have been used on a mark above building.

Although the divigin has been based upon the Pennas I believe. Since a read Systems (PSS) 550 reason has the US, trapes had a year to Area See seed and the US, trapes had a year to Area See seed and a read on his and, for a year type. One are all reading beautiful above reading above reads and layer to the trapes of the pennas of the area of the pennas of the penn

The design, anothered by several peer review of all there is again of completion, provides the claim of the in high degree of the instant generality. Not only in the large degree of the instant generality. Not only in the large degree of the instant generality and the large degree of the instant generality and the large degree of the instant generality of the large degree of the large degree of the instant general the large degree of the instant general the large degree of the large degree of the instant general the large degree of the larg

The assumptions, developments and absolute decided with this project have been shared with the bright a region as well as the countries and a section of paper to the 2000 Consortin Conference.













Associate Professor Stefano Pampanin

National Hazard Research Platform: Resilient Buildings and Infrastructure





Benefit/Risk Matrix

PRESSS Ltd.

Issue:	Option One	Option Two	Option Three	Option Four
Propping	As per traditional frame, plus additional delay for pre-stressing	Similar to traditional frame but reduced strike time due to pre- tensioning of beams	None	None
Pre-stressing	Draped tendon duct placement accuracy/tolerance required, plus difficult "saddle" across central columns	Simple straight tendon	Simple straight tendon	Simple straight tendon
Speed	Similar to traditional frame + pre- stressing time	Similar to traditional frame + pre- stressing time	Similar to a steel frame	Similar to steel frame 8 days P&G Saving 2-3 weeks site saving
Offsite risks	Typical plus draped tendon duct accuracy	Typical	Precast column hole positions and beam ends need close tolerance 2-5mm - (CAD cut plates)	Typical
Onsite risks	Duct joints/column duct placement	Duct joints/column duct placement	Fit (if not pre- QA'd/preassembled) Column erection/bracing	Column erection/bracing
Client benefits	Expected benchmark	Lower risk site work	Less site noise "Retrofit-able" system after major shake	Faster Less site noise "Retrofit-able" system after major shake
ESD benefits	Self centring building with lower structural damage and lower floor accelerations	As Option 1	Option 1, plus retrofittable, demountable and prefabricated off site	Option 1, plus retrofittable, demountable and prefabricated off site
Relative cost	QS priced to date	Additional pre-tensioning strand over QS price. Less site propping	Additional strand and hardware over QS price. Significantly lower site costs	\$300-\$350k over Option 2













Expectation Meets Reality:

Seismic Performance of Southern Cross Hospital
Endoscopy PRESSS-Building
after Feb 22 Earthquake

Stefano Pampanin and Kam Weng
University of Canterbury



Gary Haverland and Sean Gardiner
Structex Metro Ltd













NZ's second PRESSS-Building and World's first **REAL Earthquake Test**













The Building



- Southern Cross Hospital Ltd : Endoscopy Consultants Building
- Budget: \$7.2M
- 4-storey building including half depth basement
 - Car parking at basement & level 1
 - Theatres at level 2 on extended floor plate
 - Fit out on level 3
 - Additional plant room floor located at roof level
- Building footprint 19.3m x 30.2m. Gross floor area 2940m²
- Designed as Importance Level 3 structure (1/1000yrs)

The Team



Client:

Project Manager:

Architect:

Structural Engineer:

Services Engineer:

Principal Contractor:

rost rensioning oub c

Peer Reviewer:

Southern Cross Hospitals

Pragmatix

Warren & Mahoney

Structex

Beca

Fletcher Construction

Post Tensioning Sub-contractor: Fulton Hogan

Stefano Pampanin (PRESSS Ltd/

University of Canterbury)



Advantages (1/2)

Proposed PRESSS structure with the following (anticipated) advantages:

- No plastic hinges resulting in very little structural damage
- Building structure is self centering resulting in very little residual lean following an earthquake
- Building accelerations are lower than a RC frame or shear wall building resulting in less risk of damage to contents



Advantages (2/2)

- More rapid construction time as less insitu concrete on site
- Construction uses conventional building components such as precast beams, walls, drossbach ducts & starters
- Lower foundation actions resulting in pile savings
- Reduced wall reinforcing, tendon replacement
- Overall anticipated (then confimed) comparable (if not reduced) costs








Wall Coupling (UFPs)

















Excellent Performance after Feb 22



Precast walls top edges – minor crushing







Continuous functionality and immediate re-occupancy















Isn't this the GOOD NEWS

that our Society deserves to receive?



ASSOC. PROF. STEFANO PAMPANIN

NZ Society for Earthquake Engineering Incorporated

Earthquake Engineer






Why not in Timber?





The Timber "Revolution"



- •<u>Post-tensioned tendons/bars</u> (typical high strength steel or FRP) with alternative longitudinal profile (straight, draped/parabolic)
- •Internal or external reinforcement (also used as dissipaters)













Engineered Wood Products

Laminated Veneer Lumber - LVL Glued Laminated - GluLam Cross Laminated - X-Lam

Prestressed Laminated
















"Controlled rocking" mechanism












Associate Professor Stefano Pampanin


UFPs Coupled Post-tensioned Walls













(Again) From theory... to Practice












Associate Professor S

World's First Pres-Lam Building: NMIT, Nelson

















Associ


















Massey Univ, Wellington





Architect: Athfield Architects

Engineer: Dunning Thornton

QS: Rider Levett Bucknall





Massey Univ, Wellington









Platform: Resilient Buildings and Infrastructure



First Pres-Lam Building that could have appeared in Europe

Il sistema Pres-Lam dabutta in Europa con il Patazzo dell'Ambiente vinto da Archest

Provincia di Parma, uffici in legno hi-tech

erida liveripia di Persa apalita. Maggiori prima indiarrapa di Masi. na parestro Pendonin han realiza parespresa, mile

programa in General Maria de Granda de Paris. to a stage of the sale of the CC of important of the place of the co-mic for the common to the territory.

he if the property the countries of a paperty factor in the party from the fallende - det gyptione in metgin Sent or the Court of the Court g Breto Bail, allem galle sette A

Table proposed in their set on payment infraregular transfer.






Contract to the Contract of Section States and Persons of Contract of the Contract of Cont er fellent men eine fellen er, de pen finnen auch mitte den fel bei Leben meter bei bei der felt gebenfan dauer bei bei bei

ACCOMPANIES AND ACCOMPANIES OF A STATE OF A E TOUR SHOW


ACTION OF THE PROPERTY OF THE PARTY. months and the contemporary in process and the contemporary and the contemporary of the contemporary and the conte August for the set of the Colorest Colo











nt Buildings and Infrastructure







How Much do they cost?











Considerations on cost (-efficiency)

- Overall cost-comparable to their traditional counterparts
- The more they are being developed and constructed (learning the ropes) the more they can result in less expensive whilst higher performance solutions
- Material cost approximately the same of conventional solutions (Post-tensioned costs is balanced up by some lower section sizes).
- Quantity Surveyors might for the first applications tend to identify and predict higher premium due to the novelty of the system and lack of comparison with previous case

Fundamental benefits (often over-looked)

- Larger spans, bigger open space, higher interstorey
 height can result in significant occupancy benefits and
 thus financial advantages
- Speed of construction can lead to significant savings (mortgage, earlier selling, less crew on site etc)
- Advantage of higher seismic performance was often (prior to the Chch EQs) not "rewarded", whilst now it is more clearly understood and appreciated
- Reduced direct (due to damage and repairing costs) and indirect (business interruption) losses can result in significant savings (e.g. beyond cost of the structure itself)
- The latter now fundamental to negotiate a reduced level of insurance premium (of just guarantee insurance coverage)



Christchurch Vision 2050: Re-building with damage-resisting technology



























TIME FOR A RADICAL STEP-UP



THE WORLD is **HELPING**.. and **WATCHING**

We must give a **Strong Example**




Thanks for your attention


Appendix A:

Extension of of PRESSS-technology to other materials

Adaptation to Post-Tensioned Steel Connections




Adaptation to Post-Tensioned Steel Connections




Ricles, Sause et al. (Lehigh University)

Post-tensioned Steel beams and Concrete columns



(b) PT beam-column connection and RFP details.


Chou and Chen (Taiwan)




(c) Concrete strut in connection.



Post-tensioned Steel beams and ConcreteSteel (CFT) columns



Chou and Chen (Taiwan)






Appendix B:

How can we use this new technology to Retrofit Existing Buildings?

















NZ FRST-Funded Project "Retrofit Solutions" (2004-2010)









Pre 1970 Concrete Buildings

Seismic Assessment

Seismic Retrofit Solutions

FRP

Metallic Haunch

Post-Tensioned Rocking-Dissipative Walls

Selective Weakening

Seismic Risk Analysis and **Retrofit Strategies** at Territorial Scale

Damage Scenario


(PI-Stefano Pampanin)








Preparation of a Retrofit Design Handbook (End of 2012?)
















Retrofit of existing pre-1970s RC frames using Post-tensioned (rocking-dissipative wall)




Associate Professor Stefano

V_{existing frame} V_{wall}

and Infrastructure



Retrofit A



Retrofit A-Limitations

•Residual displacements

Retrofit B-Benefits

System re-centring

Near field protection

Foundation protection

Design flexibility


Minimal physical damag

Physical Damage

Existing RC frame

New Monolithic wall


b) Retrofit with monolithic wall



a) Bare frame

 V_{b}

Retrofit B



Did DCC

c) Retrofit with advanced rocking wall









New Post-tensioned wall



National Hazard Research Platform: Resilient Buildings and Infrastructure



From theory... to Practice






















Associate Professor Stefano Pampanin

2850 Telegraph Ave Berkeley, CA

- •6-story 1970 nonductile concrete frame
- •Reinforced masonry in-fills
- •< 1 mile from Hayward Fault














2850 Telegraph

UNIVERSITY OF CANTERBURY Te Whare Wananga o Waitaha

- Voluntary upgrade
- No exterior modifications
- •UC Berkeley seismic criteria
- •New walls resist all loads



Floor Plan































TIPPING MAR







































RETROFIT = STRENGTHENING?

Why not **WEAKENING?**















Failure mechanisms in walls



UNIVERSITY OF CANTERBURY

The surgery intervention...







Vertical saw-cutting














Selective Weakening for wall systems

(Report 2007: experimental validation,

Ireland, Bull, Pampanin, 2007





As built solution







Retrofitted solution using the proposed selective weakening strategy